



Drum Pumps

yts-pump.com

Features

Available in a range of sizes and materials suitable for pumping directly from 200 litre Barrels.

For the safe clean and efficient transfer of all kinds of liquids including; Corrosive Chemicals, Oils, Lubricants, Waste liquids, Solvents, Paints, Inks, Diesel, and other Fuels.

Available with 1/4" 3/8" 1/2" 3/4" and 1" pump connections.

Available in; Pure PP, GFRPP, Conductive PP, PVDF, PTFE, Aluminium, SUS & Electro Polished SUS.

Max Flow Rate up to: 220 L/min.

Max Slurry Size up to: 6.5mm.

Max Liquid Discharge Pressure: 0.7MPa

ATEX available on some models.

Fully Bolted Construction & Machined Mating Surfaces.

Designed & Manufactured in Japan.

For more information: sales@yts-pump.com

D250S

1" SUS Drum Pump
(Multiport as standard)
220 L/min Max Flow Rate
PPG Air motor.



Drum Bung Adapter (SUS)

D101S

3/8" SUS Drum Pump
(Multiport as standard)
23 L/min Max Flow Rate
Aluminium Air Motor.



D152C-X

1/2" Conductive PP
Drum Pump
56 L/min.



D050ST-X

1/4" SUS Drum Pump
11.5 L/min Max Flow Rate
PPS Air Motor.



YTS®


- ❑ Air Powered Double Diaphragm Pumps Manufactured in Japan with Superior Quality & Finish.
- ❑ Designed for High Performance Operation & Long Life Expectancy.
- ❑ Engineered with Design Features Not Often Found in Other Brand Pumps.

AODD Pump Capabilities.

Self Priming.	Variable Discharge Pressures.	Inherently Safe Design.
Run Dry.	Transfer Liquid Slurries.	Portable & Easy to Use.
Run to Dead Head.	Transfer Large Sized Solids.	Transfer Viscous Fluids.
Variable Flow Rates.	Handle Abrasives.	Frequent Start Stop Operation.
Shear Sensitivity.	Transfer Chemicals.	Powered by Compressed Air.

For more information about YTS Pumps please contact: sales@yts-pump.com

©YTS Co Ltd Japan. All Rights Reserved 2020



ATEX Compliant II 2GD c T5



JQA-QMA14279

091